



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
25.09.1996 Bulletin 1996/39

(51) Int. Cl.⁶: **G06K 19/06**

(21) Application number: **95203430.4**

(22) Date of filing: **10.10.1990**

(84) Designated Contracting States:
DE FR GB IT

(30) Priority: **05.01.1990 US 461881**

(62) Application number of the earlier application in
accordance with Art. 76 EPC: **90119399.5**

(71) Applicant: **SYMBOL TECHNOLOGIES, INC.**
Bohemia New York 11716-3300 (US)

(72) Inventors:
• **Pavlidis, Theodosios**
Setauket, NY 11733 (US)

• **Wang, Ynjuin Paul**
Port Jefferson Station, NY 11766 (US)
• **Swartz, Jerome**
Old Field, NY 11733 (US)

(74) Representative: **Maggs, Michael Norman et al**
Kilburn & Strobe
30 John Street
London WC1N 2DD (GB)

Remarks:

This application was filed on 09 - 12 - 1995 as a
divisional application to the application mentioned
under INID code 62.

(54) **High density two dimensional symbol set**

(57) A nonvolatile electro-optical read-only memory includes a substrate on which is printed (or otherwise inscribed) a complex symbol or "label" with a high density two-dimensional symbology, a variable number of component symbols or "codewords" per row, and a variable number of rows. Codewords in alternating rows are selected from mutually exclusive subsets of a mark pattern such as a (17.4) mark pattern. The subsets are defined in terms of particular values of a discriminator function, which is illustrated as being a function of the widths of bars and spaces in a given codeword. In the illustrated embodiment, each subset includes 929 available codewords; that, plus a two-step method of decoding scanned data, permitting significant flexibility in defining mappings of human-readable symbol sets into codewords. The memory may be used in conjunction with a scanner and a suitable control system in a number of applications, e.g., robotic operations or automated microfilm searching.



FIG. 3

Description**1. Background of the Invention**

5 The present invention relates to a method of reading and decoding a machine readable symbol, the symbol including a plurality of adjacent groups of codewords, each group comprising a plurality of individual codewords having a detectable mark/space pattern. It further relates to apparatus for reading and decoding such symbols. Typically, the symbol is printed or otherwise inscribed on a substrate, thereby defining a non-volatile electro-optical read-only memory. The symbol or "label" typically has a high density two-dimensional symbology, a variable number of component
 10 symbols or "codewords" per line, and a variable number of lines.

1.1 Bar Code Symbology

A bar code is typically a linear array of elements that are either printed directly on an object or on labels that are affixed to the object. As shown in Figures 1 and 2, bar code elements typically comprise bars and spaces, with bars
 15 varying widths representing strings of binary ones and spaces of varying widths representing strings of binary zeros. Many bar codes are optically detectable and are read by devices such as scanning laser beams or handheld wands. Other bar codes are implemented in magnetic media. The readers and scanning systems electro-optically decode the symbol to multiple alphanumeric characters that are intended to be descriptive of the article or some characteristic thereof. Such characters are typically represented in digital form as an input to a data processing system for applica-
 20 tions in point-of-sale processing, inventory control, and the like. Scanning systems of this general type have been disclosed, for example, in US Patent Nos. 4,251,798; 4,360,798; 4,369,361; 4,387,297; 4,409,470 and 4,460,120, all of which have been assigned to the same assignee as the instant application.

Most bar codes presently used contain only five or six letters or digits, no more than a typical vehicle license plate.
 25 In view of the relatively small amount of data contained in a typical linear bar code, the most typical applications of a bar code is to use the encoded data merely as an index to a file or data base associated with the computer system comprehensive information is available.

As noted above, the contrasting parallel bars and spaces (referred to herein as "marks") or typical optically-detectable bar codes have varying widths. Generally, the bars and spaces can be no smaller than a specified minimum width, termed the code's "unit" (or "x dimension" or "module"). While the theoretical minimum unit size is the wavelength of the
 30 light being used to read the bar code, other practical limitations exist. Among those limitations are the desired depth of field of the reading equipment, the limitations of a given printing process, and the robustness of the printed image to be correctly read despite dust, dirt, and minor physical damage.

The bar code symbols are formed from bars or elements typically rectangular in shape with a variety of possible
 35 widths.

The specific arrangement of elements defines the character represented according to a set of rules and definitions specified by the code or "symbology" used. The relative size of the bars and spaces is determined by the type of coding used, as is the actual size of the bars and spaces. The number of characters per inch represented by the bar symbol is referred to as the density of the symbol. To encode a desired sequence of characters, a collection of element arrange-
 40 ments are concatenated together to form the complete bar code symbol, with each character of the message being represented by its own corresponding group of elements. In some symbologies a unique "start" and "stop" character is used to indicate where the bar code begins and ends. A number of different bar code symbologies exist. These symbologies include UPS/EAN, Code 39, Code 93, Code 128, Codebar, and Interleaved 2 of 5.

1.2 Symbologies of (n,k) Type

Some bar codes are referred to as belonging to the (n,k) family defined by Savir and Laurer in "The Characteristics and Decodeability of the universal Product Code," IBM Systems Journal, Vol. 14, No. 1, 1973. A code of the (n,k) type represents characters uniquely by a string of n bits each containing k runs of one bit (i.e., k bars) and k runs of zero bits
 50 (i.e., spaces). An (n,k) code is decodable in both directions, i.e., by scanning it either forwards or backwards. Such bar codes are often referred to by numbers n and k; for example, the well-known Code 93 derives its name from this (n,k) notation, i.e., n = 9 and k = 3. The UPC code is an example of a (7,2) code, i.e., n = 7 and k = 2.

1.3 Prior Two-Dimensional Bar Codes

Known two-dimensional bar codes exist that are extensions of one-dimensional bar codes, in that one-dimensional bar codes are stacked with horizontal guard bars between them to increase the density. An example of such bar codes is seen in U.S. Patent No. 4,794,239, to Allais.

An obstacle to increasing the density of two-dimensional bar codes is the need for a certain minimum height in the vertical direction. A minimum height is needed to ensure that a human operator can keep a "scan line: (i.e., the path of a given scanning motion, such as that achieved by passing a hand-held wand across a bar code) within the area of a single bar-code row. Figure 1 illustrates this difficulty: scan lines 10, 11 and 12 present identical exemplar paths of, e.g., hand-held wands over the bar code 15, 16, 17. It will be seen that with a tall bar code 15, the scan lines 10 all stay within the confines of one bar code row, whereas with shorter bar codes 16 or 17, the scan lines 11 and 12 cross from one row to another.

Another limitation seen in some known two-dimensional bar codes is the use of fixed maps to translate from code-words to characters. The fixed maps restrict the flexibility of applications. For example, the well-known Code 49 has six fixed maps (i.e., six modes) to translate a codeword numerically or alphanumerically.

Although such two dimensional bar codes provide some increase in the storage capacity, such codes are still used as indices for file look-up, rather than as a complete data file in itself.

Still another drawback of some known two-dimensional codes is the need for a fixed number of codewords per line (referred to here as a "row") and the limitation of a maximum number of rows. For instance, Code 49 (a bar code generally in accordance with the aforementioned Allais '239 patent) has 4 codewords per row and 8 rows maximum.

Yet another problem is the lack of flexibility in choosing a suitable security system. (The term "security" is commonly used to refer to confidence in accuracy or correctness; it is usually specified by a misdecode rate, e.g., in errors per million.) Code 49, for example, provides a very high level of security while sacrificing about 30% of its codewords on average for checking errors. In some applications however, a lesser degree of security may be an acceptable trade-off in return for a greater codeword density; the ability to vary the security would be advantageous.

The closest prior art is represented by US-A-4794239 relating to a multitrack bar code symbol and an associated decoding method. That document discloses a method of reading and decoding a machine readable symbol, the symbol including a plurality of adjacent individual code words having a detectable mark/space pattern; the code words together defining, when taken in sequence, an encoded version of the data to be decoded, the method comprising:

- (a) scanning and reading the codewords, not necessarily in the said sequence;
- (b) calculating, for each codeword X, a discriminator function $f(X)$;
- (c) dividing the scanned codewords into a plurality of partial scans;
- (d) recreating the said sequence by stitching together the partial scans; and
- (e) decoding the codewords and outputting or storing the sequenced decoded data.

2. Summary of the Invention

The present invention enables the use of an improved high-density two-dimensional symbology, as well as a flexible method for using the symbology to encode and decode data. The symbology may be used to create a nonvolatile read-only memory, which in turn may be used in a computer system.

Prior codes have been restricted in terms of information capacity or density. The present invention allows the use of symbologies which may achieve storage capacity of up to 1 kilobytes of memory within an area of one to four square inches. The significance of such a memory one should not be underestimated - it represents about 250 English words, about the size of a page or screen display. As an information unit, such unit is most suitable for many applications.

2.1 Summary of Label Row-Wise Organization

A suitable exemplary two-dimensional label for use with the method and apparatus of the invention may comprise multiple rows of codewords; that is, the term "label" is used here to mean a complex marking of specified dimensions that includes a number of codewords organized in rows. Each codeword is a mark pattern comprising a plurality of elements or marks; the marks can be of various heights, as in a bar code, or can be of a relatively small height to form a "dot code". Not just any mark pattern can constitute a codeword, however; each codeword belongs to a specific family or "set" of mark patterns that conforms to a particular descriptive rule about some characteristic of each mark pattern, e.g., a rule about the width of each mark and the total width of each mark pattern.

The codewords in any two adjacent rows are written in mutually exclusive subsets of the mark-pattern set (although in some embodiments the union of the subset is not exhaustive of the set itself). In particular, each subset of the mark-pattern set is defined so that it includes, as valid codewords for that subset, only those mark patterns that satisfy certain discriminator-function criteria.

Such row-wise usage of alternating subsets of codewords, grouped according to discriminator-function criteria, permits quick determination whether a row has been crossed, without the need for a horizontal guard bar. This is, for a given scanned codeword in a label, determination of the discriminator function indicates whether the codeword comes from the same row as the previously-scanned codeword or from a different row (that is, whether the scan line has crossed between rows as illustrated in Figure 1).

Detection of line-crossing permits "stitching" of partial scans of particular rows into a map (e.g., in memory) of the label. The stitching process is roughly analogous to stitching a number of pieces of colored fabric into a predesigned quilt that displays, e.g., a picture: as each "piece" is required by the scanning process, it is incorporated piecewise into the appropriate point of the label.

For example, suppose that computation of the appropriate discriminator functions reveals that a scanning pass has scanned the first half of row 1 and the second half of row 2 of a label such as is shown in Figure 3. Assume that the respective longitude of the scanned data with respect to the ends of the label are known, e.g., through detection of start-and/or stop-codes. The knowledge that a row boundary has been crossed permits all the scanned data from the scanning pass to be incorporated into the respective proper rows of the label map at the respective proper longitudes (assuming no scanning or decoding errors); the data from the scanning pass need not be discarded merely because the data did not come from a single desired row.

As another (greatly simplified) hypothetical example, assume that a part of one row has been scanned and that the data "123456789" are incorporated into the label map as a result. Further assume that a second scanning pass of that row is made, and that the data "6789ABCD" are decoded as a result. If the overlapping portion if any between the two scanned data "pieces" - in this case, the "6789" portion - can be determined (e.g., with string-matching techniques such as described below), then the remainder of the later-scanned data can be approximately incorporated into the label map (in this case, the "ABCD" portion).

Consequently, the operator need not be scrupulously careful to sweep the wand over the label one row at a time; virtually any scanning pass that includes either a row's start code or a stop code, or that can somehow be determined to overlap with data already incorporated in the label map, will yield usable data (assuming no coding or decoding errors). Such a label thus advantageously increases the density of information by permitting height reductions in the codewords.

2.2 Summary of Organization of Codeword Subsets

As noted, above, a key feature of the invention is the use of different codeword subsets, preferably in different rows, each subset satisfying certain discriminator-function criteria. In one embodiment described here for illustrative purposes, a (17,4) symbology is used. A discriminator function is used to divide the 11,400 available mark patterns in that symbology into three mark pattern subsets of 929 codewords each.

The discriminator function may take as its inputs the various widths of the on- and off marks of a mark pattern (e.g., optically detectable bars and spaces) and may provide as an output a number from 0 to 8. Three subsets may then be selected whose discriminator function values are 0, 3, and 6, respectively, and whose mark widths meet certain other criteria. Each subset thus comprises a collection of codewords, all of whose discriminator functions are both equal to each other and readily distinguishable from those of the codewords in the other two subsets.

The availability of 929 codewords in each subset, each with a unique discriminatory-function number, permits each codeword to be used to represent a two-digit number in base 30. This capability leads to several advantages.

As shown in Figure 5, each digit of the two-digit base-30 number can be used in an "alpha mode" or in a "mixed mode"; that is, each digit can be mapped into a 30-place alphabetic translation table of into a 30-place mixed alphanumeric translation table. In each of these 30 place tables, one or more digits are reserved for use as signals to change translation tables.

Alternatively, each two-digit number can be used in a "numeric mode" or in a "user mode" that is, each number can be mapped into a 929-place numeric translation table or into any of up to twenty-seven 929-place user-defined translation tables. In each of these tables as well, one or more digits are reserved for use as signals to begin using a different translation table.

2.3 Summary of Two-Step Decoding Method

In the first step of the preferred method, when a codeword is scanned, the discriminator function of the scanned codeword is computed to determine the codeword subset of which the scanned codeword is a member. A t-sequence number based on the width of the marks comprising the codeword is also computed; that number is used as an entry point into a lookup table for the codeword subset in question. The lookup table yields a number from 0 to 928, which is parsed into a two-digit number in base 30.

In the second step, the high- and low-order digits of the base-30 number are used to determine the symbolic meaning assigned to the codeword (which may include an instruction to change translation tables).

The method of the invention thus advantageously permits the user to define multiple translation tables. In addition, the invention is not constrained by logical limits on the number of codewords per row nor on the number of rows. This gives the user freedom to lay out the symbology in areas of varying shapes.

2.4 Summary of Error Detection and Correction

A row-oriented incremental error detection capability is provided through the use of a checksum codeword for each row. After completion of low-level decoding but before performance of high-level decoding, various checksum computations are performed to test the accuracy of the scan.

In addition, a "final" checksum codeword for the label as a whole is used for additional security. The use of these checksums permits a limited degree of error recovery, since the checksums reflect the information contents of each of the codewords in the label. That is, errors in decoding particular codewords can be corrected in some circumstances by "subtracting" the known correct codewords from the checksum, so to speak, thereby yielding the correct value for the erroneously decoded codeword.

If the test results are satisfactory, the high-level decoding step is performed.

2.5 Summary of System Implementation

The present invention may be applied within a system for reading bar code symbols or the like, including a hand-held scanning unit in a lightweight, portable housing including a symbol-detection device for generating a laser beam directed toward a symbol to be read, and for receiving reflected light from such symbol to produce electrical signals corresponding to data represented by the symbol; a data processing device for processing the data represented by the symbol having a state according to at least first and second different coding procedures; and a read-control device to actuate the symbol-detection device to initiate reading of a symbol; wherein the symbol includes at least two groups of codewords; each codeword representing at least one information-bearing character and being selected from among a set of valid mark patterns. Each mark pattern comprises a pattern of marks, each mark pattern being representative of encoded data according to one of a plurality of different coding procedures; the codewords in each group being selected from a subset of mark patterns, the subset for said group being defined by a specified rule for that group that differs from the rule specified for said a different group each coding procedure being a function of the state of the data processing device.

3. Brief Description of the Drawings

Figure 1A is an illustration of a prior-art bar code symbology.

Figure 1B is an illustration of a label in accordance with the present invention;

Figure 2 is an illustration of the relationship between an x-sequence and a t-sequence in a codeword comprising part of a label embodying the present invention;

Figure 3 is an exemplar layout of an illustrative high density two-dimensional symbology design in accordance with the invention;

Figure 4 is a block-diagram illustration of the use of alternate sub-symbologies in different rows of a multi-row label in accordance with the invention;

Figure 5 is a table showing alternate translation modes for encoding or decoding codewords;

Figure 6 is a state-machine diagram of aspects of a method for using the table shown in Figure 5;

Figure 7 is a pictorial representation of a sequence of encoding a string of readable characters into scannable codewords;

Figure 8 is a logic diagram of an illustrative circuit for computing a checksum for a row in a label embodying the invention; Figure 9 shows a similar circuit for computing an additional checksum for the entire label.

Figure 10 is a schematic illustration of the layout of codewords within a label;

Figures 11 through 13 are logic diagrams of illustrative circuits for performing error recovery in accordance with the invention;

Figures 14A through 14D, Figures 15A through 15D, and Figures 16A through 16D depict tables used for decoding codewords in three different sub-symbologies.

Figure 17 is a C-language program that may be used to generate these tables;

Figure 18 is a block diagram of a computer system using a nonvolatile electro-optical memory in accordance with the invention;

Figure 19a, 19b, 19c, and 19d is an alternative type of laser scanning pattern that may be used in connection with the present invention;

Figure 20 is an alternative arrangement of a bar code symbol; and

Figure 21 is a cross-sectional view of an implementation of a hand-held laser scanner which may be used to implement the present invention.

4. DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

4.1 Stitching of Partial Scans

The label of the invention proves especially useful for stitching together of partial scans. As noted above (and referring to Figure 1), when scan lines cross codeword rows in a label, the partial scans must be "stitched" or pieced together. For example, consider a retail store checkout counter where a sales clerk manually passes a hand-held wand over a multirow label. If the wand's travel does not run substantially parallel to the label, the scan line may pass from one row to another; parts of different rows are thus scanned, but neither row is scanned completely.

Stitching entails building a map of each row of the label (e.g. in memory); successive passes of the wand result in a greater degree of filling in the map. It can be accomplished by using known string matching algorithms, such as disclosed in D Sankoff and J B Kruskal, editors, *Time Warps, String Edits, and Macro-molecules: The Theory and Practice of Sequence Comparison*, Addison-Wesley, Reading, Massachusetts, 1983. One such algorithm is described below.

4.2 Partitioned Symbolology

Stitching is facilitated by using different sub-symbolologies in alternate rows, selected so that the scanner can make a local decision on whether a row has been crossed. Using different sub-symbolologies in alternate rows allows the elimination of horizontal guard bars seen in prior-art code symbolologies, thus permitting high density of information.

The illustrative embodiment of the present invention utilizes an advantageous scheme for organizing codewords into readily distinguishable groups. The scheme makes use of the principle of coding theorem to pick only a fraction of available mark patterns as legal code words to increase decoding reliability; it can be applied to any of a number of labels.

One such label, referred to here as a "PDF417" label (for "Portable Data File 417"), is described as an illustration of this invention. PDF417 is a (17,4) label of the (n,k) type described above. Each codeword has 4 bars and 4 spaces with a total width of 17 modules.

It can be shown that this code yields a set of 11,440 different combinations of mark patterns. To increase decoding reliability, only a fraction of these available mark patterns are used as valid codewords.

4.3 Discriminator Function for Defining Subset Partition

As a first step in selecting a group of mark patterns for such use for this particular code, the 11,440 mark patterns are partitioned into nine subsets or "clusters," by calculating a discriminator function $f(X)$ for each mark pattern X :

$$f(X) = (x_1 - x_3 + x_5 - x_7) \bmod 9$$

where x_1, x_3, x_5 and x_7 stand for the bars' widths, and x_2, x_4, x_6 and x_8 stand for the spaces' widths. The discriminator function $f(X)$ above is one of possible alternative equations used to subdivide the different possible combinations into nine different subsets.

Further narrowing is performed on three of the nine subsets of mark patterns, namely the subsets in which $f(X)=0$, $f(X)=3$, and $f(X)=6$ (sometimes called cluster(0), cluster(3) and cluster(6), respectively). The narrowing is performed in part by defining a "t-sequence" for each mark pattern. Each element t_k of the t-sequence is computed according to the formula:

$$t_k = x_k + x_{k+1} \text{ where } k = 1, \dots, 7$$

The three subsets cluster(i) (where $i = 0, 3, 6$) are narrowed by selecting mark patterns where no mark width x_j is more than six (where $j = 1, \dots, 7$), and where no t_k is more than nine (where $k = 1, \dots, 7$).

Thus, the three final subsets cluster(i) of the mark patterns X that are selected for use as code words can be summarized as follows:

$$\text{cluster}(i) = \{x \mid f(X) = i, x_j \leq 6, t_k \leq 9\}$$

where $i = 0, 3, 6$, $j = 1, \dots, 7$, and $k = 1, \dots, 7$. After sorting each cluster by the t-sequence while suppressing duplicate entries, it can be shown that each cluster(i) includes at least 934 mark patterns. The closest prime number to 934 is 929; accordingly, 929 mark patterns are selected from each cluster(i) for use as codewords. (For convenience, the term "x-sequence," with respect to any given mark pattern, is defined as the number having its digits $x_1 x_2 \dots x_9$).

The t-sequence of each codeword can be used to identify that codeword, since it can be shown that each such t-sequence is unique within the three subsets cluster(i). It will be apparent that only the first six digits of the seven-digit t-

sequence need be used to uniquely specify a codeword of the (17,4) type, since as illustrated in Figure 2, the value of the final t-sequence element t_7 is completely determined by the first six elements t_1 and the fixed total Σx_j of the mark pattern. As an example, suppose that $t_1=2$, $t_2=4$, $t_3=6$, $t_4=7$, $t_5=6$, and $t_6=4$; the t-sequence for that codeword would be 246764.

The partition just described has the advantage that, by computing $f(X)$ for any scanned mark pattern, the mark pattern's membership (or non-membership) in a codeword subset can quickly be ascertained. Furthermore, since the t-sequence for each codeword is unique, computation of the t-sequence permits that value to be used in a lookup table to determine the symbolic meaning assigned to a scanned mark pattern that belongs to a codeword subset.

Other equivalent discriminator functions $f(X)$ may be constructed and used. Preferably, such a discriminator function should partition the available mark patterns into clusters (not necessarily nine clusters) approximately uniform in size. In addition, the clusters selected for use as codewords preferably are equidistant in "error distance", that is, the probability that a codeword from any of selected clusters A, B, C, etc., will be mistaken for a codeword from another one of those clusters should be of the same order of magnitude regardless of which of the other clusters is considered.

4.4 Generating Subsets of Codewords

An example of a computer program for generating lists of codewords for the various clusters(i) is set forth in Figure 17. The example program is written for convenience in the well-known C programming language, although any suitable language may be used; the example program is used generally as follows:

1. The program of Figure 17 is used to generate 9 output files, referred to here as out(i), where $i = 0, \dots, 8$. Only the output files out(0), out(3), and out(6) are used; they may be renamed as "cluster" files cluster(0), cluster(3), and cluster(6), respectively.
2. All three cluster files are conventionally sorted to remove ambiguous entries, i.e., to eliminate any mark pattern whose t-sequence is identical to the t-sequence of any other mark pattern.
3. The cluster files cluster(3) and cluster(6) are conventionally filtered to remove those entries in which any t_k is wider than 9.
4. In the cluster file cluster(0), those odd entries (i.e., the first entry, third entry, etc) in which any t_k is wider than 6 are filtered out, as are those even entries in which any t_k is wider than 7. This is an arbitrary restriction designed to help make cluster(0) approximately the same size as cluster(3) and cluster(6), inasmuch as without such a restriction cluster(0) would be larger than the other two.
5. The first 929 t-sequences of each of the filtered cluster files are selected as the desired entries for the respective lookup tables.

4.5 Multirow Label Using Alternating Codeword Subsets

In the multirow label of the invention, each row uses codewords from a different subset than the rows immediately adjacent to it. This enables the scanner to recognise with a high degree of precision whether a scan line has crossed a row in the middle of a codeword, because if a row has been crossed, the codewords scanned will not yield the same $f(X)$ as the previous row.

A row of codewords in accordance with the invention may conveniently contain unique start and stop codes in the conventional manner whose x-sequences are, e.g., 81111113 and 71121113 respectively. These start and stop codes are unique in that no other codeword in any cluster has the same t-sequence as either of them; furthermore, they are members of none of the final subsets of codewords because the required condition $x_j \leq 6$ for all $j = 1, \dots, 8$ is not true for those codes. The start code may be selected to have its widest bar away from the ensuing data codewords to reduce the possibility of intercodeword interference, as is the above start code; if desired, the stop code may be so selected as well.

The height unit module ratio H (the ratio of the height of a codeword (or a row) to one module width) may be changed from label to label or even from row to row depending on the printing/scanner (system or channel) resolution, R, or on the need of various applications. Figure 3 shows the first and the last rows having H approximately equal to 10, the rows in between having H approximately equal to 3, and the resolution R being approximately equal to 10 mil.

The first row of the multirow label uses cluster(0) codes, the second row cluster(3) codes, the third cluster(6) codes, the fourth cluster(0) codes, the fifth cluster(3) codes, and so on. There is no logical limit on the number of codewords per row or the total number of rows.

In the embodiment illustrated here, the first codeword in each row is dedicated for use as a row identifier and the last codeword in each row is a checksum. (The maximum number of rows is thus 929, i.e., the number of codewords in the dedicated cluster). It is of course possible to distinguish between forward scanning and backward scanning of the row by matching the start/stop codeword forwardly or backwardly.

4.6 Other Row-Wise Partitioning of Codewords

It will be apparent to those of ordinary skill having the benefit of this disclosure that the invention is not limited to the specific mark patterns, discriminator function $f(X)$, and t-sequence described above. The foregoing method of deriving a symbology can be applied in a substantially similar manner to yield equivalent symbologies having other kinds of mark patterns.

For example, labels can be constructed from bars of varying shades of gray or even from bars of a wide range of colors, instead of from black and white marks only. In such a label, a discriminator function for dividing all possible mark patterns into mutually exclusive codeword subsets, and a t-sequence function for uniquely identifying each codeword within a subset, may be based on a readily detectable attribute of a mark such as its hue or its gray scale value as well as on the width of each mark (or in lieu of the width, or in combination with the width).

It will likewise be apparent that broadly construed, the same principle encompasses the equivalent use of codewords of different colors (or shades of gray) in alternate rows. That is, all rows of a multi-row label could use the same subset of mark patterns as codewords, but in different colors or shades or orientations; the determination whether a row has been crossed would be made based on whether a color or shade or orientation change had occurred.

4.7 Subset Organization for Two-Step Decoding

In the illustrative, width-based embodiment described above, since each cluster(i) includes 929 codewords, each t-sequence in a cluster thus will correspond to a number from 0 to 928. The codewords in each subset can be organized according to a base 30 system in which one codeword, representing a number in base 30, is used to signify two alphanumeric characters.

Codewords can be scanned and decoded as follows. When a codeword is scanned, its t-sequence is noted. The t-sequence is then used as input to an initial, low-level decoding step; the output from the low-level decoding step is a number from 0 to 928 which in turn is used as an input to a high-level decoding step.

4.8 Initial Low-Level Decoding Step

The low-level decoding step entails looking up the t-sequence in a table for the appropriate cluster to find a corresponding value. The table may be created as described above. Referring to Figure 14A (a lookup table for cluster(0)), for example, the t-sequence 246764 corresponds to the value 111.

The actual circuitry for the lookup tables may be conventional; it will be appreciated by those of ordinary skill that the use of a prime number of codewords in a subset, e.g., 929, advantageously facilitates the design of the circuitry.

4.9 Mode-Dependent High-Level Decoding Step

The look-up value 111 from the foregoing example can be broken down into a two-number sequence in base 30, each number being in the range of 0-29 and having a high-level value V_H and a low-level value V_L . The base-30 sequence is computed as follows:

$$V_H = x \text{ div } 30; \text{ and}$$

$$V_L = x \text{ mod } 30.$$

For the t-sequence used above, 246764, yielding a look-up value of 111, the high level value is 3, and the low level value is 21, since $111 = 3 \times 30 + 21$. Each of the high and low values (i.e., 3 and 21) is then evaluated by looking it up in a suitable (arbitrary) table, such as shown in Figure 5.

The exemplar table in Figure 5 shows 30 decoding modes, including Alpha, Numeric, Mixed, and User modes. The various User modes are designated as the modes in Figure 5 corresponding to columns 3 through 29 (with column 0 being Alpha mode).

In the illustrative embodiment, the Alpha mode is the default mode; therefore, the sample t-sequence 246784 ultimately translates into the two-letter sequence DV, via the lookup value 111 and the base-30 sequence 3,21.

It will be seen that the coding arrangement depicted in Figure 5 provides for mode switching that can be advantageously effected either within a single codeword or within a string of codewords. The technique for invoking mode switching varies depending on the current decoder mode.

4.10 Examples of High-Level Decoding

The state machine diagram in Figure 6 illustrates a high-level decoding process in accordance with the invention for the exemplar embodiment. For convenience, a two-number sequence in base 30 is represented as "xxH xL" or "(xxH, xL)", where "xx" represents an arbitrary one or two-digit number. For example, a high-level value of 18 and a low-level value of 10 is depicted herein as 18H, 10L or as (18H, 10L).

As an example, assume the decoder is currently in Alpha mode. As shown in Figure 5, changing from Alpha mode to Mixed mode required that either the high value or the low value of the two-digit base-30 sequence be equal to 28. If the high value is 28, then the low value is unimportant for mode switching purposes; likewise, if the low value is 28, then the high value is unimportant for mode switching purposes.

For Alpha mode, a high value of 28 signals to the decoder that a mode switch to Mixed mode (depicted in Figure 5 as "ms" or Mixed-mode switch) must be effected; therefore, the low value of the high value/low value pair will be interpreted in the Mixed mode. A low value of 28 allows the decoder to interpret the high value of the high value/low value pair in the current mode, namely Alpha mode, and then to switch into Mixed mode. This mode switching technique allows a final value to be decoded in the current mode before switching to the next mode, therefore, eliminating waste resulting from using an extra high value/low value pair to insure that a final high value is interpreted in the current mode.

With decoding being done in Alpha mode, a hypothetical value of 856 yields 28H 16L, i.e. a high value of 28 and a low value of 16 (since $856 = 28 \times 30 + 16$). The high value of 28 toggles the decoder into Mixed mode, and the low value 16, when translated according to Mixed mode protocol, yields "!" (an exclamation point).

To change from Alpha mode to User mode, a high value of 29 (depicted as "us" or User-mode switch) and any low value n within the range of 3 to 29 is required. Low values of 0, 1, or 2 result in no mode switch, a switch to Mixed mode, or a switch to Numeric mode, respectively. In contrast to switching from Alpha to Numeric or Mixed modes, a switch to a User mode cannot be done by a low value of 29; any such values are ignored.

Switching between other modes is done in a generally similar manner, as shown in Figures 5 and 6. Referring to those Figures, a decoder in Numeric mode can only directly switch to Alpha mode or Mixed mode. To toggle from Numeric mode to Alpha mode a non-position dependent value of 927 is required, i.e., either a high-level value or a low-level value equal to 927 will effect the mode switch. Likewise, to toggle from Numeric mode to Mixed mode a non-position dependent value of 928 is required. It will be apparent that the numbers 927 and 928 are the last two positions in the Numeric mode, and are reserved for mode-switching characters for convenience.

To change from User mode to one of the predefined modes (Alpha, Numeric or Mixed) a high value of 29 and a low value within the range 0 to 2 is required. The low value in this combination corresponds to the predefined mode into which the decoder is switching (i.e. a low value of 0 corresponds to Alpha mode, a low value of 1 corresponds to Mixed mode and a low value of 2 corresponds to Numeric mode).

For example, assume that the current mode is Alpha and that three consecutive codewords are to be decoded: 872, 345 and 99. Translating into base 30, 872 yields a high level value of 29 and a low level value of 2 ($872 = 29 \times 30 + 2$). The first codeword 872 thus defines a User mode into which the decoder is switching. Referring to Figure 5, if the decoder is in Alpha mode and a high level value of 29 and a low level value of 2 are encountered (as in the example above), the decoder changes to Numeric mode.

As another example, assume that the decoder is in Alpha mode and that the scanned codeword's lookup value is 723. In this case $V_H = 723 \div 30 = 24$, and $V_L = 723 \bmod 30 = 3$. Therefore, the decoded codeword is (24H, 3L). Since the current mode is Alpha, Figure 5 yields (Y, D) as the respective values for the decoded codeword (24H, 3L).

Decoding of values in the Numeric mode differs from decoding of values in Alpha mode and Mixed mode. Decoding in Numeric mode treats a two-number sequence as a number in base 926. For example, suppose that the current mode is Alpha and that the following three codewords are encountered 872, 345 and 99. A base 30 conversion of the first codeword 872 yields $H = 29$ and $L = 2$. This sequence signals the decoder to switch from Alpha mode to Numeric mode. Switching to the radix-926 decoding system, the second and third codewords are decoded as $(345 \times 926) + 99 = 319569$.

The User modes may be used with considerable flexibility. All or part of one or more modes may be used to represent a special user-defined code; for example, frequently-occurring words, phrases, sentences, paragraphs, etc., can be assigned to respective positions within a User mode. A given phrase etc., can be represented in the label as a single codeword (combined with a "us" mode-switch command if necessary). It will be apparent that a great many different words, phrases, etc., can be represented, e.g., in the coding scheme depicted in Figure 5 as illustrations.

4.11 Encoding Method

An encoding procedure is the reverse process of the decoding procedure. For example, referring to Figure 6, a license plate number "HUD-329" when encoded yields the following string of codewords: 230, 926, 843, 69. Each element of the original string "HUD-329" is located in Table 2 and translated according to proper mode protocol. The first four elements of the string are translated using Alpha mode. This results in $H=7$, $U=20$, $D=3$, and (hyphen) =26.

The last three elements may be translated using Mixed mode. To switch to Mixed mode from Aopha mode a Mixed Shift (28) character is needed. The Mixed-mode translation then results in 3=3, 2=2 and 9=9. The complete string is thus 7 20 3 26 28 3 2 9.

This string is partitioned into high value/low value pairs, with resulting pairs (7,20) (3,26) (28,3) and (2,9). Each of these pairs is encoded as a codeword. To encode a high value/low value pair, the high value is multiplied by 30, and the low value is added to the result of this multiplication.

For example, the pair (7,20) is encoded by multiplying 7 times 30 and adding 20, yielding a result of 250. All four pairs are encoded in this manner; the resulting string is 230 116 843 69. The string is translated into codewords in accordance with the appropriate lookup table for the codeword subset in use. Assuming hypothetically that cluster(0) is in use, the string is expressed using the codewords corresponding respectively to t-sequences 335633 (for 230), 255663 (for 116), etc.

4.12 Checksum Computation

A checksum and error recovery scheme provides a row-oriented incremental error detection capability and high primitive decoding reliability. Within each row, a long polynomial division checksum scheme is used.

For convenience, each i -th codeword may be referred to by a corresponding index number a_i , i.e., by the result of the low-level decoding step discussed above for that codeword. Each codeword's index number a_i will thus have a value from 0 to 928; each codeword is referred to sometimes for convenience by its index number.

Each row with codewords $a_{n-1}, a_{n-2}, \dots, a_0$ can be represented as a polynomial;

$$a(x) = a_0 + a_1x + a_2x^2 + \dots + a_{n-1}x^{n-1}$$

This polynomial is referred to herein as the message polynomial, as discussed in, e.g., Shin Lin & D.J. Costello, Jr., Error Control Coding, 1983.

A row checksum b_{r0} is defined as the remainder resulting from dividing the message polynomial $a(x)$ by a generator polynomial (see *ibid.*):

$$g_r(x) = x + 926$$

Those of ordinary skill will recognize that 926 is the complement of 3 in a Galois Field based on 929, or GF(929).

The checksum of each row can conveniently be computed using the checksum encoding circuit shown in Figure 8. In Figures 8 through 13, the circle-plus (modula addition), circle-X (modulo multiplication), and circle-C (modulo complementation) symbols are defined over GF(929) as:

$$x \text{ (circle-plus)} y = (x + y) \bmod 929$$

$$x \text{ (circle-X)} y = (x * y) \bmod 929$$

$$\text{(circle-C)} x = 929 - x$$

where x and y are any numbers from 0 to 928. It will of course be recognized that the design and construction of actual circuitry is a matter of routine implementation by those of ordinary skill. Such circuitry consequently is not further discussed here.

To perform the checksum computation, the register b_{r0} is initialized to 0. The input is a sequence of codewords' index numbers a_i in a row, fed one number at a time into the input. The input fans into the output line (e.g., to a label printer) and the checksum encoding circuit simultaneously.

As the first codeword is input, the circle-plus computation is performed with the codeword's number a_i sequence and b_{r0} (i.e., 0) as operands. The output of that computation and the number 926 is fed to the circle-X computation; the input of that computation is complemented and stored in the b_{r0} register. After all of the codewords in a row have been processed through the checksum encoding circuit, the complement of the final value of b_{r0} is the checksum and is appended at the end of the row. The sequence of codewords for the row (e.g., as printed) is now $a_{n-1}, a_{n-2}, \dots, a_0, 929 - b_{r0}$.

A similar scheme is used to compute a structure checksum, one representing the entire label. For this second type of checksum, all codewords in the label as printed (including the codewords representing the checksums for each row except the last row) form the message polynomial, which may be expressed as:

$$a(x) = a_{m,2} + a_{m,3}x + \dots + a_{m,n-1}x^{n-3} + b_{m-1,r0}x^{n-2} + \dots + a_{1,n-1}x^{nm-3}$$

where the coefficients are defined as in Figure 10, tracing backwardly from right to left and bottom to top. A different generator polynomial is used to calculate a remainder in a similar fashion as before, namely:

$$g_s(x) = (x + 926)(x + 920)$$

Dividing the new message polynomial by this new generator polynomial results in a remainder $b(x) = b_{s0} + b_{s1}x$. Complementing the coefficients of this remainder yields two parity-check codewords, which serve as a structure checksum as discussed below.

In implementation this division is accomplished by using a division circuit such as shown in Figure 9. The registers b_{s0} and b_{s1} are initialized as zeros. As soon as the message polynomial has entered the output and the circuit, the complements of the parity-check codewords are in the registers and are appended in the order b_{s1} , b_{s0} just before the checksum of the last row. Then the checksum b_{r0} of the last row is computed and appended to the end of the last row, as shown in Figure 10.

It will be noted that there are no user-definable codewords corresponding to the positions $a_{m,1}$ and $a_{m,0}$. These positions are reserved for the codewords $b_{s,1}$ and $b_{s,0}$ as shown in Figure 10. Thus, in a label with m rows and no codewords per row, the total number of user-definable codewords is $nm-4m-2$, i.e., the number of codewords per row times the number of rows, minus four codewords for each row (a start code, a stop code, a row number, and a row checksum), and also minus the two parity-check codewords (i.e., the structure checksum).

4.13 Gross Error Detection

Gross error detection may be accomplished as follows. At the beginning of the scanning process, all entries (e.g., "slots" or "grid locations") of the map of the label are initialized to indicate unknown characters.

The low-level decoding step, as applied to a signal generated by any given scanning pass, will generate a sequence of one or more index numbers, one for each codeword that was scanned. Each index number may be any number from 0 to 928, depending on the t -sequence of the corresponding scanned codeword.

For each scanning pass, three arrays DA, CA, and FA are constructed (e.g., in memory in accordance with conventional techniques) to represent the codewords scanned in that pass:

- A "decoding array" DA represents the index numbers that are obtained from the tables in Figures 14A through 16D and that correspond to the scanned codewords.
- A "cluster array" CA represents the clusters or subsets to which the respective scanned codewords belong.
- A "confidence array" FA represents the confidence existing in the accuracy of the decoding of the respective scanned codewords.

For example, a scanning pass and low-level decoding step may generate a decoding array DA comprising a sequence of index numbers such as (293, 321, 209, 99, 679). The corresponding sequence of clusters might be (3, 3, 0, 0, 0) indicating that the first two codewords were members of cluster(S) and the final three were members of cluster(0). This implies that the subsequence comprising the second and third codewords (represented by 321 and 209 in the array DA) bracket the point at which a row was crossed, i.e., that the two codewords are in two adjacent rows. Because such row-crossing subsequences frequently have higher error probability, they are assigned a relatively low weight in confidence array FA. In the example above, the confidence array FA for the scanned codewords might be (3, 1, 1, 3, 3).

Now suppose that a previous scanning pass had resulted in a decoding array DA of (293, 329, 222, 999, 999) for the same sequence of codewords, where 999 represents an unknown codeword whose confidence level is zero. Further assume that the confidence array FA for that previous scanning pass is (3, 3, 1, 0, 0), because the row was crossed between the third and fourth characters on that pass instead of between the second and third characters as hypothesized in the previous paragraph.

A "voting" process may be used to compare the confidence arrays for the two scanning passes to determine which results are more likely to be correct. For example, the voting rules may be as follows:

1. If two successive scans of a given codeword result in the same index number after low-level decoding, then the corresponding confidence figures in the two confidence arrays FA are added;
2. In contrast, if two successive scans result in different numbers for the same codeword, then (a) if one of the two index numbers has a higher confidence level than the other, the higher-confidence index number "survives" and is filled into the decoding array DA, but the confidence level for the corresponding position in the confidence array FA is reduced by the confidence level for the nonsurviving index number, (b) if both index numbers have equal confidence levels, then neither index number survives; instead the unknown-codeword index number 999 is used as the "surviving" index number and the confidence is reset to zero; and

3. If the index number a_i for one scan of a given codeword is 999 (representing an unknown codeword) and an acceptable index number for the other scan (i.e., an index number from 0 to 928), then the acceptable index number is kept, and the confidence level of that index number remains the same.

It will of course be appreciated by those of ordinary skill that a wide variety of conventional array and memory-management techniques may be used for creating and manipulating the arrays DA, CA, and FA. For example, the decoding array DA might be the label map itself, with a temporary array being used to hold the index numbers a_i for a new scan and with surviving index numbers from that scan being written into the appropriate position in the array DA (or perhaps not written if the same index number is already represented at that position). In such an example the cluster array CA and the confidence array FA might each be "shadows" of the decoding array DA, with as many positions in each as there are in the decoding array DA.

When the decoding array DA has been filled with an acceptable index number a_i for all codeword positions corresponding to a particular row in the label, the representation of that row in the decoding array DA is set aside. That is, regardless of the confidence that exists about the accuracy of the contents of the decoding array DA, once the row has been decoded to indicate acceptable index numbers for each codeword, no further decoding is done for codewords in that row; additional error detection proceeds as described below.

4.14 Further Error Detection and Recovery by Checksumming

Errors may still exist in the decoding array DA for a particular row even after that row is set aside. Before performing high-level decoding, the redundant information stored in the row checksums and the label checksum can advantageously be used to detect and/or recover from errors in scanning any particular codeword by a process of elimination.

Generally speaking, if all but one or two of the codewords in the entire label are known to be correct, the correct values of the unknown codewords can be computed by "subtracting" (so to speak) the values of the known codewords from the values of the checksums, which of course reflect the values of all codewords, known and unknown.

Errors in any particular row may be detected by using a syndrome divider such as shown in Figure 11. The register d_{r0} is initialised to zero. After the index numbers a_i of the scanned row are fed to the syndrome divider, the register d_{r0} indicates the detection result. If d_{r0} is equal to zero, the corresponding row was correctly scanned and its image or map in memory can be locked; otherwise, an error occurred in the scanning and decoding of the row, and the row must be rescanned. If all codewords in the label are decoded and checked without error, then the following error recovery step can be skipped.

When the total number of still-unknown codewords is less or equal to two, an error recovery scheme as follows can be invoked. The unknown codewords first are replaced in the label map with zeros. A syndrome S_i is then computed for each $i = 1, 2$. Since by hypothesis the position p_v of the unknown (i.e., erroneous) codewords is known, where $v = 1, 2$, only the values of those unknown codewords need be computed. As a first step, an error value e_{pv} is computed for each error position p_v by solving the following system of matrix equations:

$$\begin{bmatrix} S_1 \\ S_2 \end{bmatrix} = \begin{bmatrix} 3^{p1} & 3^{p2} \\ 3^{2(p1)} & 3^{2(p2)} \end{bmatrix} \begin{bmatrix} e_{p1} \\ e_{p2} \end{bmatrix}$$

If only one error exists, the system becomes overdetermined, that is, more information is present than is needed to solve the above matrix, which reduces to:

$$\begin{bmatrix} S_1 \\ S_2 \end{bmatrix} = \begin{bmatrix} 3^{p1} \\ 3^{2(p1)} \end{bmatrix} e_{p1}$$

For an assumed one-error case, if the above matrix equation system is consistent (that is, if the foregoing two matrix equations yield the same solutions), then one error does indeed exist and the solution of 3^{p1} is the error value, i.e., the correct value of the unknown codeword. Otherwise, an undiscovered second error exists in the label, and the decoding result is rejected.

After successfully solving for the error values, the complement of error values are filled into the corresponding unknown codewords' locations. Then the error detection computation is performed again for those rows containing unknown codewords. If no errors are detected, the decoding result then is taken as correct; otherwise, the decoding result is likewise rejected.

4.15 Nonvolatile Memory and Computer System

Referring to Figure 18, a nonvolatile electro-optical memory 100 may be created by marking a suitable substrate (e.g., paper) with one or more labels in accordance with the foregoing description. The memory 100 may be combined with a fixed or movable scanner 110 for use as a storage device for a suitably programmed computer such as a processor 120.

For example, a robot might have an on-board computer programmed to control the robot to perform simple tasks, such as selectively moving an object 130 by means of a manipulator 140. An on-board scanner 110 might operate as the robot's "eyes" for reading labels of the kind described above. In similar fashion, a conveyor system might include a fixed scanner 130 and a moving belt that served as the manipulator 140. The label preferably contains a list of instructions for operating the robot, with the computer on-board. The robot responding to data and instructions contained on the label.

It will of course be recognized by those of ordinary skill (having the benefit of this disclosure) that the invention is capable of being adapted to other uses and in other embodiments than the illustrative ones disclosed above. Furthermore, the invention may be implemented in numerous specific architectures. A few examples are briefly mentioned below for illustrative purposes:

- The decoder of a conventional one-dimensional scanner could be reprogrammed to perform one or more of the functions described above, e.g., by replacing a read-only memory (ROM) chip containing the programming if the scanner is so constructed;
- A scanning system could be built using a suitably programmed microprocessor or other computational unit to perform one or more of the above functions. The programming could be loaded into dynamic read-write memory (RAM), or could be "burned" into read-only memory (ROM) either on-board or out-board of the microprocessor;
- A scanning system could be built using a computation unit specially designed to perform the functions described above;
- parallel processing technology could be used to partition the work of decoding the various parts of a label;

and so forth. The actual design and construction of any particular implementation is a matter of routine for those of ordinary skill having the benefit of this disclosure, the details of which are not further discussed here.

Referring to Figure 18, a computer system including a nonvolatile memory 100 of the type described could be used in a number of applications. As an illustration, an overnight package delivery service (e.g., Federal Express, UPS, Purolator, and the like) might have certain of its package-sorting functions automated through the use of memories 100 in the form of printed labels in accordance with the foregoing, applied to packages such as the object 130 shown in the figure. In one such possibility, package shippers would fill out a waybill 100 by responding to queries posed by a suitable computer program. The program's printed output (e.g., on a laser printer or dot matrix printer) might include both a human-readable destination address and a label 100 as described above in which that information was encoded in scannable form. The shipper would affix the printed waybill 100 to the object 130 being shipped. (Other information such as the shipper's telephone number and the like could likewise be so encoded.) One of the key advantages of the high data capacity memory 100 of the present invention is that it may be created at the warehouse or loading dock by an inexpensive printer so that updated or corrected information may be applied at the point of shipment. The fact that the memory is merely a paper label means that it is inexpensive and disposable. Thus, the present invention may be implemented in conjunction with a portable terminal and thermal printer to create and print a label, even in a remote location. Such a portable terminal, connected to scanner, allows the user to scan, print, and apply the label to the article quickly and inexpensively. At various points during shipment, suitable robots could read the label 100 and, using manipulators 140, direct the object 130 appropriately; e.g., a scanner 110 could read the memory 100 to generate a signal; based on the content of that signal, a manipulator 140 controlled by a processor 120 could move the object 140 as appropriate.

A similar arrangement could be used in a warehouse inventory control system. A label of the type described could be printed or otherwise applied to or inscribed on one or more sides of a shipping carton or directly to merchandise. The label might have encoded therein as much information as desired about the specific item, e.g., its type, color, dimensions, weight, point of manufacture, lot number and so forth. A suitable robot could be used as an order-filling machine by moving within the warehouse and, using its scanner, searching for merchandise whose label indicates that it matches a specified order. (Searching could of course be in accordance with techniques now known or hereafter developed.) It will be apparent that this arrangement would permit information about specific merchandise items to be stored locally at the merchandise itself.

Another feature of the present invention is to utilize the bar code according to the present invention so that it may be affixed to an article as a means of identifying that article and associating information with the article much like a "read-only memory" or identification tag implemented in so called RF ID systems. One such implementation is to print a variety of different bar code symbols which are available in easily disposable and affixable format so that information

may be easily and quickly affixed to the article. One example of an application is in connection with the repair and service of equipment. The use of a service record is useful for quality control and documentation purposes, but it is often impractical to store detailed written records with the equipment. The use of a high density, encoded service report affixed to the equipment in the form of a two dimensional bar code is especially advantageous. The service technician may select the appropriate PDF label from a set of labels corresponding to repairs performed, and attach the label to the repaired equipment. If the equipment is returned for subsequent repairs, the service technician has the complete service history attached to the equipment in only a few square inches.

Such local storage could advantageously take the place of a separate file of information about the item, e.g., stored in a computer database and keyed to a bar-code serial number on the item. Local storage would reduce the problem of dealing with "orphan" merchandise whose serial numbers were not known to the computer database. In addition, it would permit rapid in-processing of newly-received merchandise shipments, in that complete information about the new merchandise could be scanned into the warehouse's information system, obviating the need for the shipper to generate and transmit a separate information file (e.g., on a computer tape or by hard copy) about the specified items being shipped. This would similarly be advantageous in, e.g., libraries or other organizations that regularly received shipments of books or similar objects that required cataloguing.

Another example, a nonvolatile memory and scanner system could be used for enhanced searching of microfilm rolls or microfiche sheets. Assume that a large body of text and/or graphical information is stored photographically on a roll of microfilm. An example of such information might be the thousands of documents - printed, typed, handwritten, drawn, or a combination thereof - that can be involved in a large litigation. Known computerized litigation support systems permit paralegals to summarize each document page in a database; for each document page, selected information from the database could be inscribed as a label in accordance with the foregoing on the corresponding frame of microfilm, in a corner or other appropriate location.

A microfilm reader could be equipped with (a) input means such as a keyboard by which a user could specify search criteria (e.g., in Boolean logic); (b) a fixed scanner to read microfilm labels as the microfilm was scrolled; and (c) control means to determine whether a given microfilm frame satisfied the specified search criteria. The user would then be able to view documents conveniently. In the case of multiple-reel document collections, a master index or indexes could be encoded on a separate reel; output means such as a CRT or an LCD or LED display could be used to instruct the user as to which reel to mount to locate the specific document desired.

For example, a microfilm reader with a scanner might be designed to be coupled to and controlled by a conventional desktop, laptop, or notebook computer in a conventional manner as a peripheral device (or the essentials of such a computer could be built into the reader). The computer would not need to have the entire document-summary data base available on disk storage, since the microfilm itself would contain the necessary information; it would suffice if the computer was programmed (e.g., in ROM) to perform the desired search functions using the label-encoded data from the microfilm.

Still another feature of the present invention is to provide a method for processing information by optically scanning indicia on the surface of a substrate, the indicia including a plurality of codewords scanned sequentially and organized into at least two independent scanning paths, each codeword being either an information codeword or a control codeword, and each information codeword corresponding to at least one information-containing character. A plurality of different mapping functions are provided each associating the code word with one character out of a set of different characters, with only one mapping function being active at any given time. Each codeword in any one scanning path is distinct from any codeword in an adjacent scanning path. Using such a codeword data structure, the method includes the steps of: determining whether a scanned codeword is an information codeword or a control codeword; decoding the codeword according to the mapping function if said codeword is an information codeword; and processing the codeword if the codeword is a control codeword. If the codeword is a control codeword, it identifies a new mapping function, and processing of subsequently scanned codewords take place using the new mapping function.

As an example of the different scanning paths that may be used, and a different organization of the codewords, reference is made to Figures 19 and 20.

Figure 19a, 19b, 19c, and 19d is an alternative type of laser scanning pattern that may be used in connection with the present invention.

The present invention may be implemented in a hand-held, laser-scanning, bar code reader unit such as illustrated in Figure 21. This hand-held device of Figure 21 is generally of the style disclosed in U.S. Patent 4,760,248, issued to Swartz et al, assigned to Symbol Technologies, Inc., and also similar to the configuration of a bar code reader commercially available as part number LS 8100II from Symbol Technologies, Inc. Alternatively, or in addition, features of U.S. patent 4,387,297 issued to Swartz et al, or U.S. Patent 4,409,470 issued to Shepard et al, both such patents assigned to Symbol Technologies Inc, may be employed in constructing the bar code reader unit of Figure 21. These patents 4,760,248, 4,387,297 and 4,409,470 are incorporated herein by reference. A outgoing light beam 151 is generated in the reader 100, usually by a laser diode or the like, and directed to impinge upon a bar code symbol a few inches from the front of the reader unit. The outgoing beam 151 is scanned in a fixed linear pattern, or more complex pattern such as shown in Figure 19 may be employed and the user positions the hand-held unit so this scan pattern traverses the

symbol to be read. The use of a central dark portion, such as in Fig. 19d, may be used for aiming, or other visual techniques associated with alignment. Reflected light 152 from the symbol is detected by a light-responsive device 146 in the reader unit, producing serial electrical signals to be processed for identifying the bar code. The reader unit 100 is a gun shaped device, having a pistol-grip type of handle 153 and movable trigger 154 is employed to allow the user to activate the light beam 151 and detector circuitry when pointed at the symbol to be read, thereby saving battery life if the unit is self-powered. A light-weight plastic housing 155 contains the laser light source, the detector 146, the optics and signal processing circuitry, and the CPU 140 as well as a battery 162. A light-transmissive window 156 in the front end of the housing 155 allows the outgoing light beam 151 to exit and the incoming reflected light 152 to enter. The reader 100 is designed to be aimed at a bar code symbol by the user from a position where the reader 100 is spaced from the symbol, i.e., not touching the symbol or moving across the symbol. Typically, this type of hand-held bar code reader is specified to operate in the range of perhaps several inches.

As seen in Figure 21, a suitable lens 157 (or multiple lens system) is used to collimate and focus the scanned beam into the bar code symbol at an appropriate reference plane, and this same lens 157 may be used to focus the reflected light 152. A light source 158 such as a semiconductor laser diode is positioned to introduce a light beam into the axis of the lens 157 by a partially-silvered mirror and other lenses or beam-shaping structure as needed, along with an oscillating mirror 159 which is attached to a scanning motor 160 activated when the trigger 154 is pulled. If the light produced by the source 158 is not visible, an aiming light may be included in the optical system, again employing a partially-silvered mirror to introduce the beam into the light path coaxially with the lens 157. The aiming light, if needs, produces a visible-light spot which is scanned just like the laser beam; the user employs this visible light to aim the reader unit at the symbol before pulling the trigger 154.

In real applications, either the length of bar code should be fixed, or an additional character should be placed in the bar code to indicate its length. If not, misdecodings may occur.

If the length of the bar code is fixed, the performance of decoding using stitching might be better than that of decoding using a complete scan, because the reject rate and the misdecode rate is less in most good quality bar code (in cases that the quality of the bar code is very very poor, the misdecode rate may be greater, but never greater than 2K times, K is the number of the scans used for stitching).

Although the present invention has been described with respect to multiple line bar codes, it is not limited to such embodiments. It is conceivable that the method of the present invention may also find application for use with various machine version or optical character recognition applications in which information is derived from other types of indicia such as characters or from the surface characteristics of the article being scanned.

In all of the various embodiments, the elements of the scanner may be assembled into a very compact package that allows the scanner to be fabricated as a single printed circuit board or integral module. Such a module can interchangeably be used as the laser scanning element for a variety of different types of data acquisition systems. For example, the module may be alternately used in a hand-held scanner, a table top scanner attached to a flexible arm or mounting extending over the surface of the table or attached to the underside of the table top, or mounted as a subcomponent or subassembly of a more sophisticated data acquisition system.

The module would advantageously comprise a laser/optics subassembly mounted on a support, a scanning element such as a rotating or reciprocating mirror, and a photodetector component. Control or data lines associated with such components may be connected to an electrical connector mounted on the edge or external surface of the module to enable the module to be electrically connected to a mating connector associated with other elements of data acquisition system.

An individual module may have specific scanning or decoding characteristics associated with it, e.g. operability at a certain working distance, or operability with a specific symbology or printing density. The characteristics may also be defined through the manual setting of control switches associated with the module. The user may also adapt the data acquisition system to scan different types of articles or the system may be adapted for different applications by interchanging modules on the data acquisition system through the use of the simple electrical connector.

The following claims are intended to encompass all such uses, implementations, and embodiments.

A nonvolatile electro-optical read-only memory includes a substrate on which is printed (or otherwise inscribed) a complex symbol or "label" with a high density two-dimensional symbology, a variable number of component symbols or "codewords" per row, and a variable number of rows. Codewords in alternating rows are selected from mutually exclusive subsets of a mark pattern such as a (17,4) mark pattern. The subsets are defined in terms of particular values of a discriminator function, which is illustrated as being a function of the widths of bars and spaces in a given codeword. In the illustrated embodiment, each subset includes 929 available codewords; that, plus a two-step method of decoding scanned data, permitting significant flexibility in defining mappings of human-readable symbol sets into codewords. The memory may be used in conjunction with a scanner and a suitable control system in a number of applications, e.g., robotic operations or automated microfilm searching.

Claims

1. A method of reading and decoding a machine readable symbol, the symbol including a plurality of groups of code-
words, arranged in a plurality of lines within the symbol, each group comprising a plurality of individual codewords
5 having a detectable mark/space pattern; at least some of the codewords together defining, when taken in
sequence, an encoded version of the data to be decoded, the method comprising:

(a) scanning and reading the codewords, not necessarily in the said sequence;
(b) calculating a function $f(X)$ the value of which distinguishes the group containing X from at least one other
10 group of codewords;
(c) determining the line in which the codeword X lies at least partially by the value of $f(X)$, and dividing the
scanned codeword into a plurality of partial scans, each partial scan consisting wholly of codewords of one
group;
(d) recreating the said sequence; and
15 (e) decoding the codewords and outputting or storing the sequenced decoded data.

2. A method as claimed in Claim 1 in which the function $f(X)$ may take a plurality of discrete values, the line in which
the codeword X falls being uniquely determined by $f(X)$.

3. A method as claimed in Claim 1 or Claim 2 in which the mark/space patterns within any given group are approxi-
20 mately equidistant in terms of error distance from the mark/space patterns within any other group.

4. A method as claimed in Claim 1 in which the codewords are arranged in a plurality of adjacent rows within the sym-
bol, the row in which the codeword X lies being determined at least partially by the value of $f(X)$.

5. A method as claimed in Claim 4 in which corresponding codewords in each group are aligned in a direction perpen-
25 dicular to the rows.

6. A method as claimed in Claim 4 or Claim 5 in which the codewords are scanned row-wise or at a skewed angle
30 thereto, the codewords X_i ($i = 1, 2, \dots$) on scanning being assigned to a common row only for so long as $f(X_i)$ remains
constant.

7. A method as claimed in Claim 4 and Claim 6 in which the values of $f(X)$ uniquely discriminate between any code-
word lying in a first row and any codeword lying in a second adjacent row.

8. A method as claimed in Claim 7 in which the respective values of $f(X)$ also uniquely discriminate between any code-
word lying in the first or second rows, and any codeword lying in a third row, adjacent to the second row.

9. A method as claimed in any one of the preceding claims in which each mark/space pattern comprises a plurality of
40 bars and spaces in which $f(X)$ is a function of the widths of the individual bars and/or spaces making up the code-
word X.

10. A method as claimed in Claim 9 in which each mark/space pattern has exactly four bars and in which

$$f(X) = (x_1 - x_3 + x_5 - x_7) \bmod 9$$

where:

x_1 = width of 1st bar
50 x_3 = width of 2nd bar
 x_5 = width of 3rd bar
 x_7 = width of 4th bar

11. A method as claimed in Claim 10 in which a scanned mark/space pattern is determined not to be a codeword if $f(X)$
55 does not equal 0, 3 or 6.

12. A method as claimed in any one of the preceding claims in which a scanned mark/space pattern is determined not
to be a codeword if any of the marks or spaces making up the pattern are wider than a specified width limit.

13. A method as claimed in any one of the preceding claims in which a scanned mark/space pattern is determined not to be a codeword if the distance between the start of any one of the marks or spaces making up the pattern, and the start of the adjacent such mark or space, is greater than a specified limit.
- 5 14. A method as claimed in any one of the preceding claims in which a scanned mark/space pattern is determined not to be a codeword if the pattern does not comprise exactly a given number of marks and spaces.
15. A method as claimed in Claim 12 in which the total width of a valid codeword is 17 units, and the width limit is 6 units.
- 10 16. A method as claimed in Claim 13 in which the total width of a valid codeword is 17 units, and the specified units is 9 units.
17. A method as claimed in Claim 14 in which the total width of a valid codeword is 17 units, and in which the said given number is 4 marks and 4 spaces.
- 15 18. A method as claimed in any one of the preceding claims comprising calculating a t-sequence for the codeword X and decoding the codeword X according to the t-sequence and $f(X)$; the t-sequence being defined as a sequence of $N-1$ digits t_i where N is the total number of marks and spaces in the pattern and t_i is equal to the measured distance between the beginning of the i th mark or space and the beginning of the next following mark or space respectively (Figure 2).
- 20 19. A method as claimed in Claim 18 in which the codeword X is decoded by looking up in a table in memory an index number which, for a given value of $f(X)$ uniquely corresponds to the calculated t-sequence.
- 25 20. A method as claimed in Claim 19 including converting the index number into respective high and low values, defined as follows:

$$V_H = (\text{index number}) \text{ div } m$$

$$V_L = (\text{index number}) \text{ mod } m$$

and decoding the codeword X as two consecutive items corresponding to entries in a further look-up table at addresses V_H and V_L .

- 35 21. A method as claimed in Claim 20 in which $m = 30$.
22. A method as claimed in any one of Claims 19 to 21 including the following steps:
- 40 (a) maintaining in memory a plurality of look-up tables corresponding to a plurality of decoding modes (eg figure 5);
- (b) maintaining a variable in memory representative of the decoding mode currently active;
- (c) when the index value for the codeword X, or the value of V_H or V_L , corresponds to a control character which specifies a new decoding mode, changing to the said new mode and updating the decoding mode variable.
- 45 23. A method as claimed in any one of the preceding claims when dependent upon Claim 4 including calculating a checksum for each row and determining that an error has occurred if the calculated checksum does not match a checksum provided by a checksum-codeword in the row.
- 50 24. A method as claimed in Claim 23 including the following steps, for each row:
- (a) scanning the mark/space patterns within the row and decoding each recognised codeword where possible, to an index value;
- (b) storing the respective index values in a decoding array (DA);
- 55 (c) repeating steps (a) and (b) until an index number has been stored in the decoding array for;
- (i) the row check sum codeword for the row; and
- (ii) all but one of the codewords in the row; and

(d) reconstructing the missing one codeword using the row checksum codeword.

25. A method as claimed in Claim 23 including the following steps:

(a) scanning the mark/space patterns within a row and decoding each recognised codeword, where possible, to an index value;
 (b) storing the respective index values in a decoding array (D);
 (c) repeating steps (a) and (b) as necessary for each row, and for all rows until an index number has been stored in the decoding array for:

(i) a symbol checksum codeword;
 (ii) all but two of the codewords in the symbol; and
 (iii) the row check sum codewords for the rows having the missing codewords; and





(d) reconstructing the missing codewords using the row checksum codewords and the symbol checksum codeword.

26. A method as claimed in any one of Claims 23 to 25 including the following steps:

(a) scanning the mark/space patterns and decoding each recognised codeword, where possible, to an index value;
 (b) storing the respective index values in a decoding array (DA);
 (c) determining a confidence level corresponding to each of the elements of the decoding array (DA) and storing the confidence levels in a corresponding confidence array (FA);
 (d) re-scanning, re-decoding, and re-determining index values and corresponding confidence values;
 (e) updating the decoding array and the confidence array according to the index values and confidence values determined at step (d) and the values in the decoding and confidence arrays.

27. Apparatus for reading and decoding a machine readable symbol, the symbol including a plurality of groups of codewords, arranged in a plurality of lines within the symbol, each group comprising a plurality of individual codewords having a detectable mark/space pattern; at least some of the codewords together defining, when taken in sequence, an encoded version of the data to be decoded, the apparatus including means for scanning and reading the codewords, not necessarily in the said sequence, means for decoding the code words and means for outputting or storing the sequenced decoded data; characterised by:

(a) means for calculating a function $f(X)$ the value of which distinguishes the group containing X from at least one other group of codewords;
 (b) means for determining the line in which the codeword X lies at least partially by the value of $f(X)$, and for dividing the scanned codewords into a plurality of partial scans, each partial scan consisting wholly of code words of one group; and
 (c) means for recreating the said sequence.






FIG. 3

row0	Cluster0
row1	Cluster3
row2	Cluster6
row4	Cluster0
row n	Cluster $(n \bmod 3) * 3$

FIG. 4

Value/Mode	Alpha	Mixed	Numeric	User(s)
0	A	0	0	user defined value
1	B	1	↑	
2	C	2		
3	D	3		
4	E	4		
5	F	5		
6	G	6		
7	H	7		
8	I	8		
9	J	9		
10	K	A		to
11	L	B		
12	M	C		
13	N	D		
14	O	E		
15	P	F		
16	Q	!		
17	R	\$		
18	S	%		
19	T	&		
20	U	*	↓	us
21	V	(
22	W)		
23	X	-		
24	Y	+		
25	Z	=		
26	.	/		
27	space	:		
28	ms	as		
29	us	us		
30			925 space as ms	as ms
to				
925				
926				
927				
928				

FIG. 5




FIG. 6




FIG. 7

FIG. 8





FIG. 9



$a_{1,n-1}$	$a_{1,n-2}$		$a_{1,1}$	$a_{1,0}$	$b_{1,r0}$
$a_{2,n-1}$	$a_{2,n-2}$		$a_{2,1}$	$a_{2,0}$	$b_{2,r0}$
$a_{m-1,n-1}$	$a_{m-1,n-2}$		$a_{m-1,1}$	$a_{m-1,0}$	$b_{m-1,r0}$
$a_{m,n-1}$	$a_{m,n-2}$		b_{s1}	b_{s0}	$b_{m,r0}$

FIG. 10




FIG. 11

Syndrome divider

FIG. 12




FIG. 13




Table I : The t-sequence table. Cluster0					
t-seq	val	t-seq	val	t-seq	val
222266	0	226655	50	244664	100
222277	1	226666	51	245542	101
222355	2	226733	52	245553	102
222366	3	226755	53	245564	103
222444	4	227722	54	245653	104
222455	5	227744	55	245664	105
222466	6	227766	56	245764	106
222477	7	233354	57	246642	107
222555	8	233365	58	246653	108
222566	9	233443	59	246664	109
222666	10	233454	60	246675	110
222677	11	233465	61	246764	111
223355	12	233476	62	247753	112
223366	13	233554	63	255552	113
223444	14	233565	64	255563	114
223455	15	233665	65	255574	115
223466	16	233676	66	255663	116
223544	17	234443	67	256652	117
223555	18	234454	68	256663	118
223566	19	234465	69	256674	119
223577	20	234476	70	257752	120
223655	21	234543	71	266662	121
223666	22	234554	72	267762	122
223677	23	234565	73	322245	123
224444	24	234654	74	322256	124
224455	25	234665	75	322267	125
224466	26	234765	76	322334	126
224533	27	235532	77	322345	127
224544	28	235543	78	322356	128
224555	29	235554	79	322445	129
224566	30	235565	80	322456	130
224577	31	235643	81	322467	131
224644	32	235654	82	322556	132
224655	33	235665	83	323334	133
224666	34	235676	84	323345	134
224755	35	235765	85	323356	135
225533	36	236632	86	323434	136
225544	37	236643	87	323445	137
225555	38	236654	88	323456	138
225566	39	236665	89	323467	139
225577	40	236743	90	323545	140
225633	41	236765	91	323556	141
225644	42	237732	92	323567	142
225655	43	237754	93	323656	143
225666	44	244442	94	324423	144
225744	45	244453	95	324434	145
225766	46	244464	96	324445	146
226622	47	244553	97	324456	147
226633	48	244564	98	324467	148
226644	49	244575	99	324534	149
				324545	150
				324556	151
				324645	152
				324656	153
				325523	154
				325534	155
				325545	156
				325556	157
				325567	158
				325634	159
				325645	160
				325656	161
				325745	162
				326623	163
				326634	164
				326645	165
				326656	166
				326745	167
				327734	168
				332255	169
				332266	170
				332344	171
				332355	172
				332366	173
				332444	174
				332455	175
				332466	176
				332477	177
				332555	178
				332566	179
				332577	180
				332666	181
				333244	182
				333255	183
				333266	184
				333333	185
				333344	186
				333355	187
				333366	188
				333377	189
				333433	190
				333444	191
				333455	192
				333466	193
				333477	194
				333544	195
				333555	196
				333566	197
				333655	198
				333666	199
				334333	200
				334344	201
				334355	202
				334366	203
				334377	204
				334433	205
				334444	206
				334455	207
				334466	208
				334533	209
				334544	210
				334555	211
				334566	212
				334577	213
				334644	214
				334655	215
				334666	216
				334755	217
				335422	218
				335433	219
				335444	220
				335455	221
				335466	222
				335477	223
				335522	224
				335533	225
				335544	226
				335555	227
				335566	228
				335577	229
				335633	230
				335644	231
				335655	232
				335666	233
				335755	234
				336522	235
				336533	236
				336544	237
				336555	238
				336566	239
				336622	240
				336633	241
				336644	242
				336655	243
				336666	244
				336744	245
				337633	246
				337655	247
				337733	248
				337755	249

FIG. 14A

Table I : The t-sequence table. Cluster0					
t-seq	val	t-seq	val	t-seq	val
343343	250	354453	300	424546	350
343354	251	354464	301	425524	351
343365	252	354475	302	425535	352
343376	253	354553	303	425546	353
343443	254	354564	304	425635	354
343454	255	354575	305	426624	355
343465	256	354664	306	426635	356
343554	257	355442	307	432234	357
343565	258	355453	308	432245	358
343665	259	355464	309	432256	359
344332	260	355542	310	432334	360
344343	261	355553	311	432345	361
344354	262	355564	312	432356	362
344365	263	355653	313	432367	363
344432	264	355664	314	432445	364
344443	265	356542	315	432456	365
344454	266	356553	316	432467	366
344465	267	356564	317	432556	367
344543	268	356642	318	433223	368
344554	269	356653	319	433234	369
344565	270	356664	320	433245	370
344576	271	356753	321	433256	371
344654	272	357653	322	433267	372
344665	273	357753	323	433323	373
345432	274	365552	324	433334	374
345443	275	365563	325	433345	375
345454	276	365663	326	433356	376
345465	277	366552	327	433367	377
345532	278	366563	328	433434	378
345543	279	366652	329	433445	379
345554	280	366663	330	433456	380
345565	281	367752	331	433545	381
345576	282	422224	332	433556	382
345643	283	422235	333	434323	383
345654	284	422246	334	434334	384
345665	285	422335	335	434345	385
345754	286	422346	336	434356	386
346532	287	422357	337	434367	387
346543	288	422446	338	434423	388
346554	289	423324	339	434434	389
346565	290	423335	340	434445	390
346632	291	423346	341	434456	391
346643	292	423435	342	434534	392
346654	293	423446	343	434545	393
346665	294	423546	344	434556	394
346754	295	424424	345	434645	395
347643	296	424435	346	435423	396
347732	297	424446	347	435434	397
347754	298	424457	348	435445	398
354442	299	424535	349	435456	399
				442555	449
				442566	450
				442577	451
				442588	452
				442599	453
				442600	454
				442611	455
				442622	456
				442633	457
				442644	458
				442655	459
				442666	460
				442677	461
				442688	462
				442699	463
				442700	464
				442711	465
				442722	466
				442733	467
				442744	468
				442755	469
				442766	470
				442777	471
				442788	472
				442799	473
				442800	474
				442811	475
				442822	476
				442833	477
				442844	478
				442855	479
				442866	480
				442877	481
				442888	482
				442899	483
				442900	484
				442911	485
				442922	486
				442933	487
				442944	488
				442955	489
				442966	490
				442977	491
				442988	492
				442999	493
				443000	494
				443011	495
				443022	496
				443033	497
				443044	498
				443055	499

FIG. 14B

Table I : The t-sequence table. Cluster0									
t-seq	val	t-seq	val	t-seq	val	t-seq	val	t-seq	val
446733	500	456643	550	533335	600	544445	650	554222	700
447522	501	456654	551	533346	601	544456	651	554233	701
447544	502	456743	552	533435	602	544534	652	554244	702
447633	503	457543	553	533446	603	544545	653	554255	703
447722	504	457643	554	534324	604	545323	654	554266	704
447744	505	457743	555	534335	605	545334	655	554322	705
453332	506	464442	556	534346	606	545345	656	554333	706
453343	507	464453	557	534424	607	545423	657	554344	707
453354	508	464464	558	534435	608	545434	658	554355	708
453365	509	464553	559	534446	609	545445	659	554366	709
453443	510	464564	560	534535	610	545523	660	554422	710
453454	511	465442	561	535424	611	545534	661	554433	711
453465	512	465453	562	535435	612	545545	662	554444	712
453476	513	465464	563	535524	613	545634	663	554455	713
453554	514	465542	564	535535	614	546423	664	554466	714
453565	515	465553	565	536524	615	546434	665	554533	715
454332	516	465564	566	536624	616	546523	666	554544	716
454343	517	465653	567	542223	617	546534	667	554555	717
454354	518	466442	568	542234	618	546623	668	554644	718
454365	519	466453	569	542245	619	546634	669	555222	719
454432	520	466542	570	542256	620	547623	670	555233	720
454443	521	466553	571	542334	621	552233	671	555244	721
454454	522	466642	572	542345	622	552244	672	555255	722
454465	523	466653	573	542356	623	552255	673	555322	723
454476	524	467642	574	542367	624	552266	674	555333	724
454543	525	475552	575	542445	625	552277	675	555344	725
454554	526	476552	576	542456	626	552333	676	555355	726
454565	527	522225	577	543223	627	552344	677	555422	727
454654	528	522236	578	543234	628	552355	678	555433	728
455332	529	522247	579	543245	629	552366	679	555444	729
455343	530	522336	580	543256	630	552444	680	555455	730
455354	531	523325	581	543323	631	552455	681	555522	731
455365	532	523336	582	543334	632	552466	682	555533	732
455432	533	523347	583	543345	633	552555	683	555544	733
455443	534	523436	584	543356	634	553222	684	555555	734
455454	535	524425	585	543367	635	553233	685	555633	735
455465	536	524436	586	543434	636	553244	686	555644	736
455532	537	525525	587	543445	637	553255	687	556322	737
455543	538	532224	588	543456	638	553266	688	556333	738
455554	539	532235	589	543545	639	553322	689	556344	739
455565	540	532246	590	544223	640	553333	690	556422	740
455643	541	532257	591	544234	641	553344	691	556433	741
455654	542	532335	592	544245	642	553355	692	556444	742
456432	543	532346	593	544256	643	553366	693	556522	743
456443	544	532357	594	544323	644	553433	694	556533	744
456454	545	532446	595	544334	645	553444	695	556544	745
456532	546	533224	596	544345	646	553455	696	556622	746
456543	547	533235	597	544356	647	553466	697	556633	747
456554	548	533246	598	544423	648	553544	698	556644	748
456632	549	533324	599	544434	649	553555	699	557422	749

FIG. 14C

Table I : The t-sequence table. Cluster3					
t-seq val	t-seq val	t-seq val	t-seq val	t-seq val	t-seq val
222563	0	234327	50	266224	100
222574	1	234338	51	266235	101
222585	2	234349	52	266246	102
222596	3	234762	53	266257	103
222663	4	234773	54	266335	104
222674	5	234784	55	266346	105
222685	6	234795	56	267324	106
222696	7	234873	57	267335	107
222774	8	234884	58	267346	108
222785	9	235427	59	267435	109
222796	10	235438	60	268424	110
223652	11	235862	61	268435	111
223663	12	235873	62	269524	112
223674	13	235884	63	277223	113
223685	14	235973	64	277234	114
223696	15	236527	65	277245	115
223763	16	236962	66	277256	116
223774	17	236973	67	277334	117
223785	18	244226	68	277345	118
223796	19	244237	69	278323	119
223874	20	244248	70	278334	120
223885	21	244259	71	278345	121
224752	22	244337	72	278434	122
224763	23	244348	73	279423	123
224774	24	244772	74	279434	124
224785	25	244783	75	322453	125
224796	26	244794	76	322464	126
224863	27	245326	77	322475	127
224874	28	245337	78	322486	128
224885	29	245348	79	322497	129
224974	30	245437	80	322553	130
225852	31	245872	81	322564	131
225863	32	245883	82	322575	132
225874	33	246426	83	322586	133
225885	34	246437	84	322597	134
225963	35	246972	85	322664	135
225974	36	247526	86	322675	136
226952	37	255225	87	322686	137
226963	38	255236	88	322775	138
226974	39	255247	89	323542	139
233227	40	255258	90	323553	140
233238	41	255336	91	323564	141
233249	42	255347	92	323575	142
233662	43	256325	93	323586	143
233673	44	256336	94	323597	144
233684	45	256347	95	323653	145
233695	46	256436	96	323664	146
233773	47	257425	97	323675	147
233784	48	257436	98	323686	148
233795	49	258525	99	323764	149
				323775	150
				324642	151
				324653	152
				324664	153
				324675	154
				324686	155
				324753	156
				324764	157
				324775	158
				324864	159
				325742	160
				325753	161
				325764	162
				325775	163
				325853	164
				325864	165
				326842	166
				326853	167
				326864	168
				326953	169
				327942	170
				327953	171
				332552	172
				332563	173
				332574	174
				332585	175
				332596	176
				332663	177
				332674	178
				332685	179
				332696	180
				332774	181
				332785	182
				333552	183
				333563	184
				333574	185
				333585	186
				333596	187
				333652	188
				333663	189
				333674	190
				333685	191
				333696	192
				333763	193
				333774	194
				333785	195
				333874	196
				334652	197
				334663	198
				354226	199
				354237	200
				354248	201
					202
					203
					204
					205
					206
					207
					208
					209
					210
					211
					212
					213
					214
					215
					216
					217
					218
					219
					220
					221
					222
					223
					224
					225
					226
					227
					228
					229
					230
					231
					232
					233
					234
					235
					236
					237
					238
					239
					240
					241
					242
					243
					244
					245
					246
					247
					248
					249

FIG. 15 A

Table I : The t-sequence table. Cluster3					
t-seq	val	t-seq	val	t-seq	val
354337	250	422576	300	433475	350
354772	251	422665	301	433486	351
354783	252	423432	302	433542	352
355226	253	423443	303	433553	353
355237	254	423454	304	433564	354
355326	255	423465	305	433575	355
355337	256	423476	306	433586	356
355772	257	423487	307	433653	357
355872	258	423543	308	433664	358
356326	259	423554	309	433675	359
356426	260	423565	310	433764	360
365225	261	423576	311	434542	361
365236	262	423654	312	434553	362
365247	263	423665	313	434564	363
365336	264	424532	314	434575	364
366225	265	424543	315	434642	365
366236	266	424554	316	434653	366
366325	267	424565	317	434664	367
366336	268	424576	318	434675	368
367325	269	424643	319	434753	369
367425	270	424654	320	434764	370
376224	271	424665	321	435642	371
376235	272	424754	322	435653	372
376246	273	425632	323	435664	373
376335	274	425643	324	435742	374
377224	275	425654	325	435753	375
377235	276	425665	326	435764	376
377324	277	425743	327	435853	377
377335	278	425754	328	436742	378
378324	279	426732	329	436753	379
378424	280	426743	330	436842	380
387223	281	426754	331	436853	381
387234	282	426843	332	437842	382
387245	283	427832	333	437942	383
387334	284	427843	334	442552	384
388323	285	432442	335	442563	385
388334	286	432453	336	442574	386
389423	287	432464	337	442585	387
422343	288	432475	338	442596	388
422354	289	432486	339	442663	389
422365	290	432497	340	442674	390
422376	291	432553	341	442685	391
422387	292	432564	342	442774	392
422443	293	432575	343	443552	393
422454	294	432586	344	443563	394
422465	295	432664	345	443574	395
422476	296	432675	346	443585	396
422487	297	433442	347	443652	397
422554	298	433453	348	443663	398
422565	299	433464	349	443674	399
				443685	400
				443763	401
				443774	402
				444552	403
				444563	404
				444574	405
				444652	406
				444663	407
				444674	408
				444752	409
				444763	410
				444774	411
				444863	412
				445652	413
				445663	414
				445752	415
				445763	416
				445852	417
				445863	418
				446752	419
				446852	420
				446952	421
				453227	422
				453238	423
				453662	424
				453673	425
				453684	426
				453773	427
				454227	428
				454327	429
				454662	430
				454673	431
				454762	432
				454773	433
				455662	434
				455762	435
				455862	436
				464226	437
				464237	438
				464772	439
				465226	440
				465326	441
				475225	442
				475236	443
				476225	444
				476325	445
				486224	446
				486235	447
				487224	448
				487324	449
				497223	450
				497234	451
				498323	452
				522233	453
				522244	454
				522255	455
				522266	456
				522277	457
				522333	458
				522344	459
				522355	460
				522366	461
				522377	462
				522444	463
				522455	464
				522466	465
				522555	466
				523322	467
				523333	468
				523344	469
				523355	470
				523366	471
				523377	472
				523433	473
				523444	474
				523455	475
				523466	476
				523544	477
				523555	478
				524422	479
				524433	480
				524444	481
				524455	482
				524466	483
				524533	484
				524544	485
				524555	486
				524644	487
				525522	488
				525533	489
				525544	490
				525555	491
				525633	492
				525644	493
				526622	494
				526633	495
				526644	496
				526733	497
				527722	498
				527733	499

FIG. 15B

Table I : The t-sequence table. Cluster3					
t-seq	val	t-seq	val	t-seq	val
532332	500	542453	550	554552	600
532343	501	542464	551	554563	601
532354	502	542475	552	554572	602
532365	503	542486	553	554583	603
532376	504	542553	554	554752	604
532387	505	542564	555	554763	605
532443	506	542575	556	555552	606
532454	507	542664	557	555562	607
532465	508	543442	558	555752	608
532476	509	543453	559	555852	609
532554	510	543464	560	563227	610
532565	511	543475	561	563662	611
533332	512	543542	562	563673	612
533343	513	543553	563	564662	613
533354	514	543564	564	564762	614
533365	515	543575	565	574226	615
533376	516	543653	566	585225	616
533432	517	543664	567	596224	617
533443	518	544442	568	622223	618
533454	519	544453	569	622234	619
533465	520	544464	570	622245	620
533476	521	544542	571	622256	621
533543	522	544553	572	622267	622
533554	523	544564	573	622334	623
533565	524	544642	574	622345	624
533654	525	544653	575	622356	625
534432	526	544664	576	622445	626
534443	527	544753	577	623323	627
534454	528	545542	578	623334	628
534465	529	545553	579	623345	629
534532	530	545642	580	623356	630
534543	531	545653	581	623434	631
534554	532	545742	582	623445	632
534565	533	545753	583	624423	633
534643	534	546642	584	624434	634
534654	535	546742	585	624445	635
535532	536	546842	586	624534	636
535543	537	552552	587	625523	637
535554	538	552563	588	625534	638
535632	539	552574	589	626623	639
535643	540	552585	590	632222	640
535654	541	552663	591	632233	641
535743	542	552674	592	632244	642
536632	543	553552	593	632255	643
536643	544	553563	594	632266	644
536732	545	553574	595	632277	645
536743	546	553652	596	632333	646
537732	547	553663	597	632344	647
537832	548	553674	598	632355	648
542442	549	553763	599	632366	649
632444	650	643354	700	632455	651
632455	651	643365	701	633222	652
633222	652	643432	702	633233	653
633233	653	643443	703	633244	654
633244	654	643454	704	633255	655
633255	655	643465	705	633266	656
633266	656	643543	706	633322	657
633322	657	643554	707	633333	658
633333	658	644332	708	633344	659
633344	659	644343	709	633355	660
633355	660	644354	710	633366	661
633366	661	644432	711	633433	662
633433	662	644443	712	633444	663
633444	663	644454	713	633455	664
633455	664	644532	714	633544	665
633544	665	644543	715	634322	666
634322	666	644554	716	634333	667
634333	667	644643	717	634344	668
634344	668	645432	718	634355	669
634355	669	645443	719	634422	670
634422	670	645532	720	634433	671
634433	671	645543	721	634444	672
634444	672	645632	722	634455	673
634455	673	645643	723	634533	674
634533	674	646532	724	634544	675
634544	675	646632	725	635422	676
635422	676	646732	726	635433	677
635433	677	652442	727	635444	678
635444	678	652453	728	635522	679
635522	679	652464	729	635533	680
635533	680	652475	730	635544	681
635544	681	652553	731	635633	682
635633	682	652564	732	636522	683
636522	683	653442	733	636533	684
636533	684	653453	734	636622	685
636622	685	653464	735	636633	686
636633	686	653542	736	637622	687
637622	687	653553	737	637722	688
637722	688	653564	738	642332	689
642332	689	653653	739	642343	690
642343	690	654442	740	642354	691
642354	691	654453	741	642365	692
642365	692	654542	742	642376	693
642376	693	654553	743	642443	694
642443	694	654642	744	642454	695
642454	695	654653	745	642465	696
642465	696	655432	746	642554	697
642554	697	655542	747	643332	698
643332	698	655642	748	643343	699
643343	699	655742	749		

FIG. 15C

Table I : The t-sequence table. Cluster3					
t-seq	val	t-seq	val	t-seq	val
662552	750	743255	800	762453	850
662563	751	743322	801	762464	851
662574	752	743333	802	762553	852
662663	753	743344	803	763442	853
663552	754	743355	804	763453	854
663563	755	743433	805	763542	855
663652	756	743444	806	763553	856
663663	757	744222	807	764442	857
664552	758	744233	808	764542	858
664652	759	744244	809	764642	859
664752	760	744322	810	772552	860
673662	761	744333	811	772563	861
722224	762	744344	812	773552	862
722235	763	744422	813	773652	863
722246	764	744433	814	832224	864
722335	765	744444	815	832235	865
723324	766	744533	816	833324	866
723335	767	745322	817	842223	867
724424	768	745333	818	842234	868
732223	769	745422	819	842245	869
732234	770	745433	820	842334	870
732245	771	745522	821	843223	871
732256	772	745533	822	843234	872
732334	773	746422	823	843323	873
732345	774	746522	824	843334	874
733223	775	746622	825	844323	875
733234	776	752332	826	844423	876
733245	777	752343	827	852222	877
733323	778	752354	828	852233	878
733334	779	752365	829	852244	879
733345	780	752443	830	852255	880
733434	781	752454	831	852333	881
734323	782	753332	832	852344	882
734334	783	753343	833	853222	883
734423	784	753354	834	853233	884
734434	785	753432	835	853244	885
735423	786	753443	836	853322	886
735523	787	753454	837	853333	887
742222	788	753543	838	853344	888
742233	789	754332	839	853433	889
742244	790	754343	840	854222	890
742255	791	754432	841	854233	891
742266	792	754443	842	854322	892
742333	793	754532	843	854333	893
742344	794	754543	844	854422	894
742355	795	755332	845	854433	895
742444	796	755432	846	855322	896
743222	797	755532	847	855422	897
743233	798	755632	848	855522	898
743244	799	762442	849	862332	899

FIG. 15D

Table I : The t-sequence table. Cluster6									
t-seq	val	t-seq	val	t-seq	val	t-seq	val	t-seq	val
222236	0	233357	50	244445	100	255555	150	268643	200
222247	1	233368	51	244456	101	256322	151	269632	201
222258	2	233379	52	244467	102	256333	152	269643	202
222269	3	233446	53	244556	103	256344	153	277442	203
222336	4	233457	54	245323	104	256355	154	277453	204
222347	5	233468	55	245334	105	256366	155	277464	205
222358	6	233557	56	245345	106	256377	156	277553	206
222369	7	234324	57	245356	107	256433	157	278542	207
222447	8	234335	58	245367	108	256444	158	278553	208
222458	9	234346	59	245378	109	256455	159	279642	209
222469	10	234357	60	245434	110	256466	160	322226	210
223325	11	234368	61	245445	111	256544	161	322237	211
223336	12	234379	62	245456	112	256555	162	322248	212
223347	13	234435	63	245467	113	257422	163	322259	213
223358	14	234446	64	245545	114	257433	164	322337	214
223369	15	234457	65	245556	115	257444	165	322348	215
223436	16	234468	66	246423	116	257455	166	322359	216
223447	17	234546	67	246434	117	257466	167	322772	217
223458	18	234557	68	246445	118	257533	168	322783	218
223469	19	235424	69	246456	119	257544	169	322794	219
223547	20	235435	70	246467	120	257555	170	323326	220
223558	21	235446	71	246534	121	257644	171	323337	221
224425	22	235457	72	246545	122	258522	172	323348	222
224436	23	235468	73	246556	123	258533	173	323359	223
224447	24	235535	74	246645	124	258544	174	323437	224
224458	25	235546	75	247523	125	258555	175	323448	225
224469	26	235557	76	247534	126	258633	176	323872	226
224536	27	235646	77	247545	127	258644	177	323883	227
224547	28	236524	78	247556	128	259622	178	323894	228
224558	29	236535	79	247634	129	259633	179	324426	229
224647	30	236546	80	247645	130	259644	180	324437	230
225525	31	236557	81	248623	131	259733	181	324448	231
225536	32	236635	82	248634	132	266332	182	324537	232
225547	33	236646	83	248645	133	266343	183	324972	233
225558	34	237624	84	248734	134	266354	184	324983	234
225636	35	237635	85	249723	135	266365	185	325526	235
225647	36	237646	86	249734	136	266376	186	325537	236
226625	37	237735	87	255233	137	266443	187	326626	237
226636	38	238724	88	255244	138	266454	188	332225	238
226647	39	238735	89	255255	139	266465	189	332236	239
226736	40	244234	90	255266	140	266554	190	332247	240
227725	41	244245	91	255277	141	267432	191	332258	241
227736	42	244256	92	255333	142	267443	192	332269	242
233235	43	244267	93	255344	143	267454	193	332336	243
233246	44	244278	94	255355	144	267465	194	332347	244
233257	45	244334	95	255366	145	267543	195	332358	245
233268	46	244345	96	255377	146	267554	196	332369	246
233279	47	244356	97	255444	147	268532	197	332447	247
233335	48	244367	98	255455	148	268543	198	332458	248
233346	49	244378	99	255466	149	268554	199	333225	249

FIG. 16A

Table I : The t-sequence table. Cluster6					
t-seq	val	t-seq	val	t-seq	val
333236	250	344246	300	355256	350
333247	251	344257	301	355267	351
333258	252	344268	302	355323	352
333269	253	344324	303	355334	353
333325	254	344335	304	355345	354
333336	255	344346	305	355356	355
333347	256	344357	306	355367	356
333358	257	344368	307	355434	357
333369	258	344435	308	355445	358
333436	259	344446	309	355456	359
333447	260	344457	310	355545	360
333458	261	344546	311	356323	361
333547	262	345324	312	356334	362
334325	263	345335	313	356345	363
334336	264	345346	314	356356	364
334347	265	345357	315	356423	365
334358	266	345424	316	356434	366
334425	267	345435	317	356445	367
334436	268	345446	318	356456	368
334447	269	345457	319	356534	369
334458	270	345535	320	356545	370
334536	271	345546	321	357423	371
334547	272	346424	322	357434	372
335425	273	346435	323	357445	373
335436	274	346446	324	357523	374
335447	275	346524	325	357534	375
335525	276	346535	326	357545	376
335536	277	346546	327	357634	377
335547	278	346635	328	358523	378
335636	279	347524	329	358534	379
336525	280	347535	330	358623	380
336536	281	347624	331	358634	381
336625	282	347635	332	359623	382
336636	283	348624	333	359723	383
337625	284	348724	334	365222	384
337725	285	354223	335	365233	385
343224	286	354234	336	365244	386
343235	287	354245	337	365255	387
343246	288	354256	338	365266	388
343257	289	354267	339	365277	389
343268	290	354278	340	365333	390
343279	291	354334	341	365344	391
343335	292	354345	342	365355	392
343346	293	354356	343	365366	393
343357	294	354367	344	365444	394
343368	295	354445	345	365455	395
343446	296	354456	346	366222	396
343457	297	355223	347	366233	397
344224	298	355234	348	366244	398
344235	299	355245	349	366255	399
				366266	400
				366322	401
				366333	402
				366344	403
				366355	404
				366366	405
				366433	406
				366444	407
				366455	408
				366544	409
				367322	410
				367333	411
				367344	412
				367355	413
				367422	414
				367433	415
				367444	416
				367455	417
				367533	418
				367544	419
				368422	420
				368433	421
				368444	422
				368522	423
				368533	424
				368544	425
				368633	426
				369522	427
				369533	428
				369622	429
				369633	430
				376332	431
				376343	432
				376354	433
				376365	434
				376443	435
				376454	436
				377332	437
				377343	438
				377354	439
				377432	440
				377443	441
				377454	442
				377543	443
				378432	444
				378443	445
				378532	446
				378543	447
				379532	448
				379632	449
				387442	450
				387453	451
				388542	452
				422227	453
				422238	454
				422249	455
				422662	456
				422673	457
				422684	458
				422695	459
				422773	460
				422784	461
				423327	462
				423338	463
				423762	464
				423773	465
				423784	466
				423873	467
				424427	468
				424862	469
				424873	470
				425962	471
				432226	472
				432237	473
				432248	474
				432259	475
				432337	476
				432348	477
				432772	478
				432783	479
				432794	480
				433226	481
				433237	482
				433248	483
				433326	484
				433337	485
				433348	486
				433437	487
				433772	488
				433783	489
				433872	490
				433883	491
				434326	492
				434337	493
				434426	494
				434437	495
				434872	496
				434972	497
				435426	498
				435526	499

FIG. 16B

Table I : The t-sequence table. Cluster6					
t-seq	val	t-seq	val	t-seq	val
442225	500	454257	550	466345	600
442236	501	454324	551	466423	601
442247	502	454335	552	466434	602
442268	503	454346	553	466445	603
442269	504	454357	554	466534	604
442336	505	454435	555	467323	605
442347	506	454446	556	467334	606
442358	507	455224	557	467423	607
442447	508	455235	558	467434	608
443225	509	455246	559	467523	609
443236	510	455324	560	467534	610
443247	511	455335	561	468423	611
443258	512	455346	562	468523	612
443325	513	455424	563	468623	613
443336	514	455435	564	475222	614
443347	515	455446	565	475233	615
443358	516	455535	566	475244	616
443436	517	456324	567	475255	617
443447	518	456335	568	475266	618
444225	519	456424	569	475333	619
444236	520	456435	570	475344	620
444247	521	456524	571	475355	621
444325	522	456535	572	475444	622
444336	523	457424	573	476222	623
444347	524	457524	574	476233	624
444425	525	457624	575	476244	625
444436	526	464223	576	476255	626
444447	527	464234	577	476322	627
444536	528	464245	578	476333	628
445325	529	464256	579	476344	629
445336	530	464267	580	476355	630
445425	531	464334	581	476433	631
445436	532	464345	582	476444	632
445525	533	464356	583	477222	633
445536	534	464445	584	477233	634
446425	535	465223	585	477244	635
446525	536	465234	586	477322	636
446625	537	465245	587	477333	637
453224	538	465256	588	477344	638
453235	539	465323	589	477422	639
453246	540	465334	590	477433	640
453257	541	465345	591	477444	641
453268	542	465356	592	477533	642
453335	543	465434	593	478322	643
453346	544	465445	594	478333	644
453357	545	466223	595	478422	645
453446	546	466234	596	478433	646
454224	547	466245	597	478522	647
454235	548	466323	598	478533	648
454246	549	466334	599	479422	649
				479522	650
				479622	651
				486332	652
				486343	653
				486354	654
				486443	655
				487332	656
				487343	657
				487432	658
				487443	659
				488432	660
				488532	661
				497442	662
				522552	663
				522563	664
				522574	665
				522585	666
				522663	667
				522674	668
				523652	669
				523663	670
				523674	671
				523763	672
				524752	673
				524763	674
				525852	675
				532227	676
				532238	677
				532662	678
				532673	679
				532684	680
				532773	681
				533227	682
				533327	683
				533662	684
				533673	685
				533762	686
				533773	687
				534762	688
				534862	689
				542226	690
				542237	691
				542248	692
				542337	693
				542772	694
				542783	695
				543226	696
				543237	697
				543326	698
				543337	699
				543772	700
				543872	701
				544226	702
				544326	703
				544426	704
				552225	705
				552236	706
				552247	707
				552258	708
				552336	709
				552347	710
				553225	711
				553236	712
				553247	713
				553325	714
				553336	715
				553347	716
				553436	717
				554225	718
				554236	719
				554325	720
				554336	721
				554425	722
				554436	723
				555225	724
				555325	725
				555425	726
				555525	727
				563224	728
				563235	729
				563246	730
				563257	731
				563335	732
				563346	733
				564224	734
				564235	735
				564246	736
				564324	737
				564335	738
				564346	739
				564435	740
				565224	741
				565235	742
				565324	743
				565335	744
				565424	745
				565435	746
				566224	747
				566324	748
				566424	749

FIG. 16C

Table I : The t-sequence table. Cluster6					
t-seq	val	t-seq	val	t-seq	val
566524	750	622442	800	674324	850
574223	751	622453	801	674335	851
574234	752	622464	802	675224	852
574245	753	622475	803	675324	853
574256	754	622553	804	675424	854
574334	755	622564	805	684223	855
574345	756	623542	806	684234	856
575223	757	623553	807	684245	857
575234	758	623564	808	684334	858
575245	759	623653	809	685223	859
575323	760	624642	810	685234	860
575334	761	624653	811	685323	861
575345	762	625742	812	685334	862
575434	763	632552	813	686223	863
576223	764	632563	814	686323	864
576234	765	632574	815	686423	865
576323	766	632663	816	695222	866
576334	767	633552	817	695233	867
576423	768	633563	818	695244	868
576434	769	633652	819	695333	869
577223	770	633663	820	696222	870
577323	771	634652	821	696233	871
577423	772	634752	822	696322	872
577523	773	642227	823	696333	873
585222	774	642662	824	697222	874
585233	775	642673	825	697322	875
585244	776	643662	826	697422	876
585255	777	643762	827	722332	877
585333	778	652226	828	722343	878
585344	779	652237	829	722354	879
586222	780	652772	830	722365	880
586233	781	653226	831	722443	881
586244	782	653326	832	722454	882
586322	783	662225	833	723432	883
586333	784	662236	834	723443	884
586344	785	662247	835	723454	885
586433	786	662336	836	723543	886
587222	787	663225	837	724532	887
587233	788	663236	838	724543	888
587322	789	663325	839	725632	889
587333	790	663336	840	732442	890
587422	791	664225	841	732453	891
587433	792	664325	842	732464	892
588322	793	664425	843	732553	893
588422	794	673224	844	733442	894
588522	795	673235	845	733453	895
596332	796	673246	846	733542	896
596343	797	673335	847	733553	897
597332	798	674224	848	734542	898
597432	799	674235	849	734642	899

FIG. 16D

FIG. 17A

../src/pdf174.c

```
#include <stdio.h>
#define MODULE 9

FILE *fopen(), *fout[9];

int t[8];
int x[8] = {0,0,0,0,0,0,0,0};
int b[13] = {0,0,0,0,0,0,0,0,0,0,0,0,0};
int m = 7;
int n = 9; /*17 - 8*/
int other = 0;
int total = 0;

int grteq(i)
int i;
{
    int k, flag;

    flag=0;
    for(k=0; k<=m; k++) if(x[k] >= i) flag=1;
    return(flag);
}
```

FIG. 17B

```

void s(i)
int i;
{
int k, sum, j, tmp;

sum=0;
for(k=0; k<i; k++) sum += x[k];
if(i == m) {
    x[m] = n - sum;
    for(k=0; k<m; k++) t[k] = x[k]+x[k+1];
    tmp = x[0] - x[2] + x[4] - x[6];
    tmp = tmp%MODULE;
    if(tmp < 0) tmp += MODULE;
    total++;
    if(grteq(6)) other++;
    else { b[tmp]++;
            for(k=0; k<m; k++)
                fprintf(fout[tmp], "%d ", t[k]+2);
            fprintf(fout[tmp], "\n");
        }
    } else {
        for(j=0; j<=(n-sum); j++) {x[i]=j; s(i+1);}
    }
}

```

FIG. 17C

```
main()
{
  int k;

  fout[0]=fopen("out0", "w");
  fout[1]=fopen("out1", "w");
  fout[2]=fopen("out2", "w");
  fout[3]=fopen("out3", "w");
  fout[4]=fopen("out4", "w");
  fout[5]=fopen("out5", "w");
  fout[6]=fopen("out6", "w");
  fout[7]=fopen("out7", "w");
  fout[8]=fopen("out8", "w");
  s(0);
  for(k=0;k<MODULE;k++) fclose(fout[k]);
}
```





FIG. 18

FIG. 19a




FIG. 19b




FIG. 19c





FIG. 19d






FIG. 20




FIG. 21